

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION
OFFICE OF THE STATE FIRE MARSHAL
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM

LISTING SERVICE

LISTING No. 3225-1328:113 Page 1 of 1

CATEGORY: Fire Dampers

LISTEE: Air Balance, 7301 International Drive, Holland OH 43528
Contact: *Chuck Schneider (419) 865-5000

DESIGN: Models FS1250, FS1350, FS2250, FS2350, FS3250, FS3350, FS4250, and FS4350 fire dampers. Parallel blade design, single and multiblade type construction. 5-1/2" x 16 Ga. galvanized steel frame; 7-3/4", 5-3/4" and/or 3-3/4" wide x minimum 16 Ga. galvanized steel blades; 1/2" square plated, galvanized or stainless steel blade axles; and 20 Ga. minimum sleeves thickness. Maximum single section is 36" wide x 50" high and multiple section is 72" wide x 50" high. Refer to listee's data sheet for additional detailed product description and operational considerations.

RATING: 1-1/2 Hour, 250°F or 350°F Temperature Degradation

INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

MARKING: Listee's name, model number, rating and UL label.

APPROVAL: Listed as 1½-hour fire-rated dampers for use in air conditioning and ventilation ducts to protect openings. For vertical and horizontal installations.

NOTE: Leakage rating not evaluated. Refer to CSFM Listing No. 3230-1328:108.

*Rev. 08-23-2001



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other suitable information sources.

Date Issued:

AUGUST 19, 2002

*Listing Expires **June 30, 2003***

Authorized By:

DIANE K. AREND, Senior Deputy
Program Manager